




01/2021


## H9-2 Series



①



②



③



④

**Hand-guided, self-propelled-marking machine for small varied marking jobs.**

- ① **H9 Sprayplastic** equipped for sprayable thermoplastics (low pressure method).
- ② **H9 Airspray** equipped for Airspray cold paints with one pressurised glass bead tank with 20 l at max. 1,0 bar
- ③ **H9-2 Airless 2c 98:2** equipped for Airless 2-component sprayable cold plastics, internal mixing and mixing ratio 98:2
- ④ **Trailer with driver seat**  
The perfect and comfortable supplement for H9-2.  
Adjustable sitting position, pneumatic tires  
Dimensions (L x W x H mm):  
900 x 740 x 1 000  
Weight: 20 kg

- Infinitely hydraulic drive. Uniform drive of front wheels by differential drive.
- Vibration isolation for motor/compressor unit.
- Fixing for marker unit right and left side.
- Pneumatic tires, foam-filled tires or full-rubber tires (as an option).
- Electronic spacing device available as an option.
- Flashlights (optional).
- Straight-run fixing device for rear wheel in order to maintain easily the direction.
- Uniform line widths, even intight bends.
- Height adjustable handle.
- Drive unit according to CE (declaration of conformity).

## Technical Data

### H9-2 Airspray

1-cylinder 390 cm<sup>3</sup>, Honda gasoline motor, air-cooled

8,4 kW at 3 200 rpm

Drive unit: Hydrostatic infinitely variable

Air output:  
Up to 670 l/min  
(2-cylinder compressor)

Pressurised glass bead container (max. 1,0 bar):  
20 l (one container)  
2 x 20 l (two container)

Dimensions (L x W x H mm):  
1 700 x 1 050 x 1 420  
(dependent on equipment)

Weight:  
approx. 340 - 370 kg /  
750 - 815 lbs

Line widths:  
10 - 60 cm  
(dependent on material and equipment)

### H9-2 Airless 2c, M98:2

1-cylinder 390 cm<sup>3</sup>, Honda gasoline motor, air-cooled

8,4 kW at 3 200 rpm

Drive unit: Hydrostatic infinitely variable

Air output:  
Up to 260 l/min  
(2-cylinder compressor)

Press.glass bead container, (max. 1,0 bar):  
20 l

Pump delivery rate:  
bis 6,0 l/min  
for mixing ratio 98:2

Dimensions (L x W x H mm):  
1 700 x 1 100 x 1 420  
(dependent on equipment)

Weight:  
approx. 440 kg /  
970 lbs

Line widths:  
10 - 30 cm  
(dependent on material and equipment)

### H9-2 Sprayplastic

1-cylinder 390 cm<sup>3</sup>, Honda gasoline motor, air-cooled

8,4 kW at 3 200 rpm

Drive unit: Hydrostatic infinitely variable

Air output:  
Up to 670 l/min  
(2-cylinder compressor)

Press.glass bead container, (max. 1,0 bar):  
20 l

Dimensions (L x W x H mm):  
2 100 x 1 500\* x 1 420  
(dependent on equipment)  
\*) incl. gas bottle holder

Weight:  
approx. 480 - 520 kg /  
1058 - 1146 lbs

Line widths:  
10 - 30 cm  
(dependent on material and equipment)

### Cold Paints:

Container  
up to 48 l (one container)  
up to 96 l (two container  
for one or two colours)

### Cold Paints:

Container  
without material container

### Sprayable cold plastics:

without material container

### Sprayable thermo-plastics:

Container  
up to 50 l

### H9-2 Airspray:

Can be equipped with additional hand spray gun. Material container with manual agitator.

### H9-2 Airless 2c, M98:2

Hardener quantity infinitely variable between 1,2 and 3,0 percentage by weight. Equipment for internal mixing (static mixer). 2c spray gun can be used also as hand spray gun. Possibility to use commercial paint buckets as an insert container.

### H9-2 Sprayplastic:

Container and gun indirectly heated by heat transfer oil which is heated by LPG. Equipment for single lines or continuous double lines. Infinitely variable adjustment of the outlet of the gun towards road surface. Marker unit with ground wheel with equipment for double lines. Available as an option: Pneumatic agitator